according to UK REACH Regulation

Multifunktionsöl Spray H1 400ml

Revision date: 12.07.2021

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Winkel Multifunktionsöl H1 400ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricant

1.3. Details of the supplier of the safety data sheet

Company name:	Winkel GmbH	
Street:	Lisztstr. Nr.1	
Place:	D-53881 Euskirchen	
Telephone:	+49 (0) 22517769400-401	Telefax: +49 (0) 22517769402
e-mail:	info@winkelgroup.de	
Internet:	info@winkelgroup.de	

1.4. Emergency telephone number:

111 NHS (National Health Service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories: Aerosol: Aerosol 1 Aspiration hazard: Asp. Tox. 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. May be fatal if swallowed and enters airways.

2.2. Label elements

GB CLP Regulation

Signal word:

Pictograms:

Danger



Hazard statements

H222 H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards



according to UK REACH Regulation

Multifunktionsöl Spray H1 400ml

Revision date: 12.07.2021

Page 2 of 10

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification				
64742-48-9	9 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics			50 - <= 100 %	
	918-481-9		01-2119457273-39		
	Asp. Tox. 1; H304 EUH066				
124-38-9	carbon dioxide			1 - < 3 %	
	204-696-9				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	iC No Chemical name			
	Specific Conc. Limits, M-factors and ATE				
64742-48-9	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	50 - <= 100 %		
inhalation: LC50 = 4951 mg/l (vapours); dermal: LD50 = >3160 mg/kg; oral: LD50 = >8000 mg/kg					

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons, < 5 % phosphates.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures



according to UK REACH Regulation

Multifunktionsöl Spray H1 400ml

Revision date: 12.07.2021

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Further information on handling

Avoid contact with skin and eyes.

Page 3 of 10



according to UK REACH Regulation

Multifunktionsöl Spray H1 400ml

Revision date: 12.07.2021

Page 4 of 10

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

blood (B) Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses. DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min Thickness of the glove material 0,45 mm

EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols. When exceeding the relevant workplace exposure limits, note the following: Suitable respiratory protective equipment: Combination filter device (DIN EN 141).. Filtering device with filter or ventilator filtering device of type: AX Observe the wear time limits as specified by the manufacturer.



0

Safety Data Sheet

according to UK REACH Regulation

Multifunktionsöl Spray H1 400ml

Revision date: 12.07.2021		Page 5 of 10
Observe legal regulations and provi	sions.	
Environmental exposure controls		
Observe legal regulations and provi	sions.	
SECTION 9: Physical and chemical p	operties	
9.1. Information on basic physical and ch	emical properties	
Physical state:	Aerosol	
Colour:	colourless	
Odour:	characteristic	
		Test method
Changes in the physical state		
Boiling point or initial boiling point and boiling range:	100 °C	
Flash point:	> 61 °C	
Flammability		
Solid/liquid:	not applicable	
Gas:	not applicable	
Lower explosion limits:	0,5 vol. %	
Upper explosion limits:	7 vol. %	
Self-ignition temperature		
Solid:	not applicable	
Gas:	not applicable	
Decomposition temperature:	not determined	
Oxidizing properties Not oxidising.		
pH-Value (at 20 °C):		DIN 19268
Viscosity / kinematic:	4 mm²/s	
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents not determined		
Density (at 20 °C):	0,805 g/cm³	DIN 51757
9.2. Other information		
Other safety characteristics		
Solid content:	not determined	
Evaporation rate:	not determined	
Further Information		
Data apply to technical substance: Rela	tive density, Colour, Odour, Viscosity, pH.	

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under normal conditions.



Page 6 of 10

Safety Data Sheet

according to UK REACH Regulation

Multifunktionsöl Spray H1 400ml

Revision date: 12.07.2021

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 >8000 mg/kg	Rat		
	dermal	LD50 >3160 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 4951 mg/l	Rat		

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].



Page 7 of 10

Safety Data Sheet

according to UK REACH Regulation

Multifunktionsöl Spray H1 400ml

Revision date: 12.07.2021

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
	Acute fish toxicity	LC50 mg/l	>1000		Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	>1000		Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna		

12.2. Persistence and degradability

There are no data available on the mixture itself. AOX (mg/l): 0

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS



according to UK REACH Regulation

Multifunktionsöl Spray H1 400ml

	Matthanktionse		
Revision date: 12.07.2021			Page 8 of 10
14.3. Transport hazard class(es):	2		
14.4. Packing group:	-		
Hazard label:	2.1		
Classification code:	5F		
Special Provisions:	190 327 344 625		
Limited quantity:	1 L		
Excepted quantity:	E0		
Transport category:	2		
Tunnel restriction code:	D		
Inland waterways transport (ADN)			
14.1. UN number or ID number:	UN 1950		
14.2. UN proper shipping name:	AEROSOLS		
14.3. Transport hazard class(es):	2		
14.4. Packing group:	-		
Hazard label:	2.1		
Classification code:	5F		
Special Provisions:	190 327 344 625		
Limited quantity:	1 L		
Excepted quantity:	E0		
Marine transport (IMDG)			
14.1. UN number or ID number:	UN 1950		
14.2. UN proper shipping name:	AEROSOLS		
<u>14.3. Transport hazard class(es):</u>	2.1		
14.4. Packing group:	-		
Hazard label:	2.1		
Marine pollutant:	no		
Special Provisions:	63, 190, 277, 327, 3	44, 381,959	
Limited quantity:	1000 mL		
Excepted quantity: EmS:	E0 F-D, S-U		
	F-D, 5-0		
Air transport (ICAO-TI/IATA-DGR)			
<u>14.1. UN number or ID number:</u>	UN 1950		
14.2. UN proper shipping name:	AEROSOLS, flamma	able	
<u>14.3. Transport hazard class(es):</u>	2.1		
14.4. Packing group:	-		
Hazard label:	2.1		
Special Provisions:	A145 A167 A802		
Limited quantity Passenger:	30 kg G		
Passenger LQ:	Y203		
Excepted quantity:	E0		
IATA-packing instructions - Passenger:		203	
IATA-max. quantity - Passenger:		75 kg 203	
IATA-packing instructions - Cargo: IATA-max. quantity - Cargo:		203 150 kg	
		130 Kg	
14.5. Environmental hazards			
ENVIRONMENTALLY HAZARDOUS:	No		
14.6. Special precautions for user			
Warning: Flammable gases.			
14.7. Maritime transport in bulk according	to IMO Instruments		
Deside No. 4.04 Destauration 4.00		NI .	Dist. 1.1. 40.07.0001



according to UK REACH Regulation

Multifunktionsöl Spray H1 400ml

Observe restrictions to employment for juveniles according to the 'juvenile

Revision date: 12.07.2021

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

2010/75/EU (VOC):

2004/42/EC (VOC):

No information available. No information available.

work protection guideline' (94/33/EC).

1 - slightly hazardous to water

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Aerosol directive (75/324/EEC)

National regulatory information

Employment restrictions:

Water hazard class (D):

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 3,4,6,9,10,13.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA: International Air Transport Association IMDG: International Maritime Code for Dangerous Goods GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average ATE: Acute Toxicity Estimate STEL (EC) Short Term Exposure Limit LC50: Lethal Concentration EC50: half maximal Effective Concentration ErC50: means EC50 in terms of reduction of growth rate

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure	
Aerosol 1; H222-H229	On basis of test data	
Asp. Tox. 1; H304	Calculation method	

Relevant H and EUH statements (number and full text)

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.

Page 9 of 10



according to UK REACH Regulation

Multifunktionsöl Spray H1 400ml

Revision date: 12.07.2021

Page 10 of 10

EUH066

Repeated exposure may cause skin dryness or cracking.

Further Information

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]: Calculation method.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)